1U Standard Chassis Energy-Saving Customs Declaration



Overview

Customs declaration As authorisation holder, you can submit a declaration in the form of an entry in your own records – if the details of that declaration.

Key Takeaways

To import or export a 1U standard chassis with energy-saving features, a proper customs declaration must be submitted, including commercial invoices, customs value declarations, and compliance with EU procedures.

Customs Declaration Overview

A customs declaration is an official document detailing goods being imported or exported into the EU customs territory. It is required to indicate the intention to place goods under an EU customs procedure, such as import, export, or transit, as defined in the Union Customs Code (UCC) (Articles 5(12) and 158–187). Declarations must generally be submitted online at the customs office where the goods are presented.

Required Documentation

For a 1U chassis, the following documents are typically required: Commercial Invoice: Records the transaction between exporter and importer, including total invoice value, currency, and product description. It should be submitted in the original with at least one copy, preferably in English. Customs Value Declaration: Required if the value of imported goods exceeds EUR 20,000.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

This form (DV1) is used to determine the customs value, including costs such as transport and insurance to the first EU entry point. Proof of Origin: Certifies the country of origin of the chassis, which may affect tariffs or preferential treatment. Export Declaration: If exporting, a customs export declaration must be created and submitted, either manually or automatically, referencing the export transaction through a Movement Reference Number (MRN).

Simplifications and Authorizations

Certain simplified procedures may apply if authorized by customs authorities, such as: Incomplete Customs Export Declarations (ICEDs) for integrated logistics transactions. Presentation waivers or other procedural simplifications for frequent exporters. Authorized declarants may submit declarations in their country of establishment even if goods are presented elsewhere in the EU.

Product Considerations

The 1U standard chassis is a rackmount server-grade unit with features like SATA hard drive support, redundant power supply, and cooling fans designed for continuous operation. When declaring such equipment: Include technical specifications and energy-saving features in the invoice or product description to ensure proper classification. Ensure compliance with EU energy efficiency regulations if applicable, as this may affect import duties or certification requirements.

Summary

To successfully declare a 1U energy-saving chassis for import/export: Prepare a commercial invoice with full product details. Submit a customs value declaration if the shipment exceeds EUR 20,000. Provide proof of origin and any required export documentation.

Consider simplified procedures if authorized. Include technical and energy-saving specifications to ensure correct classification and compliance. Following these steps ensures compliance with EU customs regulations and smooth processing of your 1U chassis shipment.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Article Content

Customs declaration

As authorisation holder, you can submit a declaration in the form of an entry in your own records – if the details of that declaration are concurrently in possession of the customs authorities.

1U | Rackmount Chassis

1U rackmount chassis is an powerful chassis. This rackmount chassis with great ventilation is especially designed for space-constrained applications. Configure your own 1U Rackmount classis to your

1U Rackmount Chassis / InWin / IW-RA100

All hardware components and optional parts are not included. InWin can customize the I/O shield backplate for specific motherboards, with SGCC material to fulfill customers'' specific I/O configuration

7190M 19” 1U Chassis Kit

The 7190M Chassis is equipped with dual hot-swappable power supplies sufficient for any combination of transmitters and receivers as specified. Power to the two installed power supplies is via two

IANOS Standard chassis 1U

Efficiently manage fiber cables with the High-Density IANOS Chassis (1U). Supports up to 12 single or 6 double modules, supports 72 ports per 1U, compatible with EDR, features front/rear module fitting

1U Chassis

The 1U chassis support multiple configurations include SATA hard drives, rackmount chassis and redundant power supply that fulfill server-grade IPC standard. The 1U chassis series with the cooling

Customs clearance documents and procedures | Access2Markets

It provides detailed information on EU import procedures, including topics such as registering as an economic operator and the Economic Operators Registration and Identification (EORI) number, the

Customs information for sending parcels internationally | DHL

For shipments to countries outside the EU, always attach carefully completed customs declarations (CN23 or CN22) to the item. The required number of customs declarations depends on the country.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

HUBER+SUHNER IANOS Standard 1U Installation Manual

View and Download HUBER+SUHNER IANOS Standard 1U installation manual online. IANOS Standard 1U chassis pdf manual download. Also for: Ianos standard 4u, Ianos lite.

IANOS Lite chassis 1U

Efficiently manage fiber cables with the IANOS Lite Chassis (1U). Easy and time-saving installation, high fiber density, perfect for medium-density applications connecting servers and switches.

Choose the Perfect Rackmount Server Case: 1U to 4U Guide

Choose 1U server chassis for maximum density and space-constrained environments with lower performance and expansion needs. Opt for 2U server chassis for a good balance of

1U Rackmount Chassis / InWin / IW-RA100

1U appliance chassis with 15" depth for space-sensitive applications Utilizing space for HDD deployment to optimized HDD storage design Outstanding thermal exhaust efficiency supports 40 x 28mm PWM

1U Rack U Rackmount Measurements | Comms Express | Comms

1U is a standard rack unit measurement. U designates rack height and the vertical space available for devices. 1U is equal to 1.75 inches.

Customs clearance documents and procedures | Access2Markets

Customs warehousing - non-Union goods may be stored in premises or any other location authorised by the customs authorities and under customs supervision (''customs warehouses'') without being

Enterprise Core Systems Engineering Reference Manual: 1U

PRODUCT IDENTIFICATION The 1U Rackmount Form Factor represents the foundational hardware chassis standard for high-density telecommunications, enterprise data center, and carrier-grade

Choosing the Right Rackmount Server Case: 1U, 2U,

Understand how 1U, 2U, 3U, and 4U rackmount server units vary in order to optimize your server requirements to select the most appropriate piece

The 2025 Guide to UK Customs Declaration Requirements

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

With continual changes to UK customs regulations, staying current with declaration requirements is essential for smooth imports and exports. At MartinTrux, we work with businesses

SCCM: System Chassis Types – The Admin Script Bank

ChassisTypes Value System Type 1 Other 2 Unknown 3 Desktop (including virtual machines) 4 Low Profile Desktop 5 Pizza Box 6 Mini Tower 7 Tower 8 Portable 9 Laptop 10

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved