Distance between vertical cable tray fixing supports



Overview

The length between support positions will change depending on the cable design, size, materials and weight.

Key Takeaways

For vertical cable tray runs, supports should be fixed to the building structure at intervals preferably less than 2 meters, with cables secured at the top and every 1. 5 meters.

Vertical Support Guidelines

When installing cable trays vertically, it is essential to ensure that the trays are securely fixed to the building structure to prevent sagging, mechanical strain, or damage to the cables. The recommended spacing between vertical supports is generally less than 2 meters, depending on the tray type, load, and cable weight (Apex Tray). Cables within vertical trays should be secured at the top of the run and then at intervals of approximately 1.

5 meters along the vertical section. This ensures that the cables remain organized, do not cross or overlap, and are not subjected to undue mechanical stress.

Key Points for Vertical Cable Tray Installation

Fixed Supports: Install at the beginning and end of the vertical run, at corners, T-junctions, and for long spans exceeding 30 meters to distribute weight evenly. Cable Securing: Use cable ties or clamps to secure cables at the top and every 1. 5 meters along the vertical run.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Structural Attachment: Supports should be anchored to walls, ceilings, or steel structures capable of bearing the combined weight of the tray and cables. Fire Safety: All supports should be made of fire-resistant materials to prevent premature failure in case of fire.

Additional Considerations

Horizontal vs Vertical Runs: While vertical runs use supports every 1. 5–2 meters, horizontal tray sections typically have support spans ranging from 1. 5 to 3 meters, depending on tray type and load.

Corners and Bends: Install one hanger on each side of bends or corners to maintain stability and prevent cable stress. Clearances: Maintain adequate vertical clearance from ceilings or other obstructions (minimum 0. 3 meters) to allow for ventilation and future cable additions.

By following these guidelines, vertical cable tray installations will maintain structural integrity, safety, and compliance with best practices, ensuring reliable cable management and ease of maintenance.

Article Content

Cable Support Distances

The length between support positions will change depending on the cable design, size, materials and weight. For example, an MDPE sheathed cable will be stiffer and therefore require a greater distance

Cable Tray Spacing Standards for Installation and Safety

When planning the vertical spacing between floor-mounted cable trays, the minimum distance should be 150 millimeters. This clearance prevents

Cable Tray Support Spacing: Key Guidelines Explained

Explore the essential cable tray support spacing requirements for safe and efficient installations. Learn NEC guidelines for perforated, ladder, and wire

Guide to cable support systems

The load capacity of the cable trays according to the support width can be read off in the diagram using load curves – here, shown as an example for a cable tray with the tray widths 100 to 600 mm.

A Guide to Installing and Supporting Electrical Cable Trays

Cable Tray Support Span: The distance between supports is a critical calculation. The cable tray support span must be determined based on the manufacturer''s

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Cable Tray Technical Guide A practical guide to product selection and ...

Cable tray length is selected based on the load to be supported, the distance between the supports (also referred to as the span), and handling and installation constraints.

Cable tray support spacing calculator

Not sure how far apart to space your cable tray supports? Use our free cable tray support spacing calculator to find the precise spacing.

Best Practice Guide to Cable Ladder and Cable Tray Systems

The radius for cable ladder and cable tray fittings is usually determined by the bending radius and stiffness of the cables installed on the cable ladder or cable tray.

Cable Fixing Distances | Horizontal & Vertical Gaps

Unicrimp explains required distances between cable fixings, helping you achieve compliant horizontal and vertical spacing in every type of installation.

Cable fixing and the 18th Edition IET Wiring Regulations

When fixing cables to exposed horizontal surfaces, the spacing of metal fixings should be approximately every 300mm. For vertical running cables that are exposed, a metal clip every 400mm

Best Practice Guide to Cable Ladder and Cable Tray Systems

Wall support brackets (Figures 12) are an effective way of fixing any width of cable ladder or cable tray, running either vertically or horizontally, to a vertical support.

Best practice guide to cable ladder and cable tray systems

Cable ladder and cable tray systems The following recommendations are intended to be a practical guide to ensure the safe and proper installation of cable ladder and cable tray systems

Guide to cable support systems

The cable support lengths and fittings can basically be designed as cable trays, cable ladders or mesh cable trays, in which cables are routed. Fittings can, on the one hand, be used for horizontal or

Cable Tray Thickness Guide: Which Thickness Should You Choose?

1. Reference Cable Tray Thickness Chart & Structural Classifications Cable support products are engineered using precise sheet steel thicknesses chosen around distinct physical load

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Precautions for Cable Tray Installation

The overall layout of the cable tray should be short distances, economic feasibility, safe operation, and meet the requirements for construction, maintenance, and cable laying. The cable tray should have

Cable Fixing Distances | Horizontal & Vertical Gaps

Q3 of 5 - What distances are required between fixings and how do you allow for horizontal and vertical distances? The guidance issued within the On-Site Guide (OSG) published by

Beama Best Practice Guide | Installation Of The System | Cable ...

Wall support brackets (Figures 12) are an effective way of fixing any width of cable ladder or cable tray, running either vertically or horizontally, to a vertical support.

Load over Span Considerations

In the case of electrical products such as cable tray or ladder (which are load rated in kilograms per metre), the span is the distance between support points,

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved