High and low level input optocoupler module



Overview

This module allows microcontrollers to safely control high-voltage devices using a relay with optocoupler isolation. It supports both HIGH and LOW level triggering, selectable via jumper, making it flexible for different logic levels. Trigger Jumper: Set to L for LOW-level trigger (default), or H. An optocoupler (also called an opto-isolator or photocoupler) is a component that transfers an electrical signal between two isolated circuits using light. Inside the package, an infrared LED on the input side shines onto a phototransistor on the output side. Because the signal crosses as light —. Extra isolation with optocoupler at the front of control and the activation logic for the relay is configurable via a mini jumper. 3V (High) activation or 0V (Low) activation. This is the universal Relay breakout board and we like it. It features an optocoupler for electrical isolation, ensuring safe operation and protection of sensitive control. The module allows the control of the actuators consuming a current of up to 10 A using the microcontroller's port or any development kit, for example, Arduino and Raspberry through the low or high status selected by the jumper.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Article Content

User''s Guide: 12V 1-Channel Relay Module (High/Low Trigger,

This module allows microcontrollers to safely control high-voltage devices using a relay with optocoupler isolation. It supports both HIGH and LOW level triggering, selectable via jumper,

PC817 Optocoupler Module User Guide | Wiring & Setup

In systems with multiple voltage rails (3.3V, 5V, 12V, 24V), use the optocoupler module to safely pass signals between voltage domains without

1CH Active H/L 3V OptoCoupler Relay Module

This is a 1 (single) channel universal 3.3V relay module because it can be configured as high or low triggered (Logic High or Low). With each relay rated at 250VAC, 10A, and breakout to screw

Optocouplers, Optoisolators | Isolators | DigiKey

Crucially, there is no direct electrical connection between input and output, which allows the optocoupler to provide galvanic isolation—protecting low-voltage

How to Use 5V 30A 1

It features an optocoupler for electrical isolation, ensuring safe operation and protection of sensitive control circuits. This module supports both high-level and

250VAC/30VDC 10A 5VDC 4-Channel Optocoupler Isolated

The module allows the control of the actuators consuming a current of up to 10 A using the microcontroller''s port or any development kit, for example, Arduino and Raspberry through the low or

12V 1 Channel Module with Optocoupler Isolation High

High and low level trigger selection ends: 1 when jumper short circuit with LOW is low lever trigger; 2 When jumper short circuit with high is high lever trigger.

8-Channel Relay Module (12VDC)| High/Low Level

8-Channel Relay Module (12VDC)| High/Low Level Trigger with Optocoupler Isolation Load DC 30V/10A AC 250V/10A for PLC quantity

DC 12V-24V Optocoupler Isolation Module 8-Channel

It is a DC 12V 24V 8-Channel Optocoupler Isolation Module can detect 8-Channel DC input power sources and output DC voltage according to the detection results.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Using Opto Couplers

Each logic family (e.g. LSTTL or CMOS types) may have different logic voltage levels and different input and output current requirements, and optocouplers can

Best Electronic Components Online Buy In Bangalore | Sharvielectronics

1 Channel 3V Relay Module High And Low Level Trigger With Opto Isolation ₹ 84.54 (Excluding All Taxes)

8-Channel 5V Relay Module Board with Optocoupler for Arduino, High/Low ...

The high-quality components minimize the risk of failure, providing consistent operation for your automated systems. □Optocoupler Isolation for Enhanced Safety□Featuring optocoupler isolation,

Reliable Solutions for Your opto isol modul Needs in Global Markets

OptoIsolation 5V 4-Channel Relay Module Supports High and Low Level Trigger Optocoupler ICs Product $1.29-1.79 Delivery by Jun 25 MOQ: 1 piece

8 Channel Relay Modules

High/Low Level Trigger Relay Module 1/2/4/6/ 8Channel 5V 12V 24V Home Intelligent Control Module Optocoupler Isolation Output $ 0.25 - 2.79 MOQ: 100 pieces Delivery by Jul 09 12 yrsCN Supplier

Prison Cell Monitor & Alert System using mmWave presence sensor

The interface is deliberately minimal. The RD-03''s OT2 pin is its sole output to the Arduino — one wire carrying a simple HIGH/LOW voltage. No UART protocol, no baud rate, no

PC817 Optocoupler Isolation 3.3V 5V, 12V, 24V

MCU output level To drive the motor When the inductive device, such as the motor, is isolated, anti-interference protects the circuit of the MCU. The output level of

Amazon : 8 Relay Module

12V Relay Module with Optocoupler Isolation, 8 Channel High/Low Level Trigger, Compatible with Arduino Raspberry Pi for DIY Projects Add to cart

12v Relay Module 4 Channel with opto-Isolated high and Low Level ...

12V 4 Channel Relay Module features high-quality relays supporting AC 250V/10A DC 30V/10A loads. SMD OPTOCOUPLER isolation provides 5mA trigger current with strong drive capability.

Related Video Reference

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved