
High-speed optical module dual-fiber LC interface



Overview

Feature highlights: High-performance SFP optical module with dual data-rate support of 1. 0625Gbps, offering 550m transmission distance over SMF. 8W), and excellent EMI ESD protection. Upgrade networks with our 10G SFP+ 80km Module. CONQUER DISTANCE: 80km Long-Range Transmission Power Subheading Focus: Transmission Distance & Wavelength Distance limits many. The 1. 25G SFP transceiver module operates at a specific wavelength, typically around 1310nm, which is commonly used in fiber optic communications. The SFP28 SR provides 25Gb/s throughput up to 100 meters on OM4 and 70 meters on OM3 multimode fiber (MMF) with host FEC using 850nm wavelength. Standard AC coupled CML for high speed signal and LVTTL control and monitor signals. The receiver section uses a PIN receiver and the transmitter uses a 1310 nm FP laser, up to. Fiber optic transceivers sfp multimode 1310nm 10km Features ● Hot-pluggable SFP footprint ● Low power dissipation ●Metal enclosure, for lower EMI ●RoHS compliant and lead-free ●Support Digital Diagnostic Monitoring interface ● Single +3. 3V power supply ●Compliant with SFF-8472 Applications ● Switch.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Article Content

10G 1550nm LC Interface Singlemode Dual-fiber SFP+ Optical Module

10G 1550nm LC Interface Singlemode Dual-fiber SFP+ Optical Module Upgrade networks with our 10G SFP+ 80km Module. This 1550nm optical transceiver offers effortless, stable long-range connectivity

SFP Optical Transceiver Module LC 1.25G-LR Dual fiber Compatible

Due to the explosive growth of data center traffic, higher-speed optical modules are required to cope with the huge traffic transmission demand. 1.25G SFP transceiver module is individually tested to be

Cisco 400G QSFP-DD Ultra Long Haul Coherent Optics Module

The media interface is a duplex LC connector over single-mode fiber coupled to a 1550-nm and 1595-nm optical fiber carrying coherent signals at up to 118 Gbaud in OpenROADM 7.0 compliant mode.

25GBASE-SR SFP28 850nm 100m – Duplex LC MMF Module

The electrical interface is an MSA-compliant 20-pin edge connector and the optical interface is a duplex LC connector. The full-duplex SFP28 transceiver features a highly reliable

1.25g 1310nm 20km Dual Fiber LC Interface SFP Optical Module

Fiber optic transceivers sfp multimode 1310nm 10km. Features. Hot-pluggable SFP footprint. Low power dissipation. Metal enclosure, for lower EMI. RoHS compliant and lead-free. Support Digital

What Is an SFP Duplex LC Connector in Fiber Networks

Learn what an SFP duplex LC connector is, how it works in optical transceivers, and why it is widely used in fiber networks for reliable full-duplex

Multi Mode Dual Fiber LC Interface 850nm 550m SFP Module

Feature highlights: High-performance SFP optical module with dual data-rate support of 1.25Gbps and 1.0625Gbps, offering 550m transmission distance over SMF. Features an LC duplex connector, low

10G Single-mode Dual-fiber LC Interface 10km 1310nm Industrial

The SFP+ transceivers are designed for use in 10-Gigabit Ethernet links up to 10km over Single Mode Fiber. The transceivers are compatible with SFP+ MSA and SFF-8472.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

1.25G SFP Module Transceiver, 1000Base-LX,1310nm

1.25G SFP MODULE- 1.25Gbps SFP Optical Transceiver, Dual LC single-mode fiber, 1310nm, up to 20km super long distance transmission for POE switch with

BRKOPT-2699

High-Speed Interconnects: Backend network requires high speed 100G/200G or 800G optics to connect servers and network switches. These high bandwidth connections are essential for handling the data

Optical Transcevier

100% Compatible, 10Gbps Data Rate DWDM SFP+ Optical Transceiver 100% Compatible, 10Gpbs Data rate, Long distance transmission 10G SFP+ dual fiber

Technology from 400G to 800G to 1.6T Transceivers

800G Fiber and 800G Ethernet are two emerging technologies as the need for high-speed data transmission in data center networks continues to

China Wholesale China Glc-Te Manufacturers Pricelist

Ang JHA''s JHA3280D Transceiver ay isang mataas na pagganap, matipid na module na may duplex LC optics interface. Standard AC coupled CML para sa high speed signal at LVTTL control at monitor

CCTV PH FORUM | DATA RATE 1.25GBPS – HIGH

DATA RATE 1.25GBPS – HIGH-SPEED FOR GIGABIT ETHERNET. 850NM VCSEL LASER – RELIABLE OPTICAL SIGNALING. 550M DISTANCE – WITH 50/125µM MMF. SFP MSA

10GBase-SR SFP+ Multimode Module, Duplex LC Connector 850Nm

10GBase-SR SFP+ : Provides ultra-fast 10Gb/s data transmission over multi-mode fiber with an 850nm wavelength, ideal for high-performance networking environments. Duplex LC Connector : Ensures

China Trending Products Bidi Tx1490nm/Rx1550nm 80km LC

Ang JHA3405D Transceiver ay isang high performance, cost effective na module na mayroong duplex LC optics interface. Standard AC coupled CML para sa high speed signal at LVTTL control at

Boost Connectivity with Reliable optic connect modul Solutions for ...

Low signal attenuation and immunity to electromagnetic interference define optic connect modul perfect for long-distance and high-speed transmission. Furthermore, these parts'' lightweight and small size

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

2018 High quality SFP+ Optical Module

Ang JHA3220D Transceiver ay isang high performance, cost effective na module na mayroong duplex LC optics interface. Standard AC coupled CML para sa high speed signal at LVTTL control at

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved