
Huawei optical module display abnormality



Overview

The optical module is faulty or not securely installed. If the transmit optical power is abnormal, replace the. The display devm/ports/port[position="GE0/0/11"]/optical-module/ all command output shows that the transmit optical power of the optical module is abnormal. "rx-high-power-warn-en": true, "rx-low-power-warn-en": true, "tx-high-power-warn-en": true, "tx-low-power-warn-en": true. Optical modules are widely used in switches, network interface cards (NICs), routers, and other communication devices. During use, reading optical module information helps understand its real-time operating status, enabling faster troubleshooting of link abnormalities. (EntityPhysicalIndex=, BaseTrapSeverity=, BaseTrapProbableCause=, BaseTrapEventType=, EntPhysicalContainedIn=, EntPhysicalName=" ", RelativeResource=" ". Run the display interface transceiver verbose command to display diagnostic information about the optical module on the local interface.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Article Content

Troubleshooting Guidelines for Optical Modules

Remove and reinstall the optical module. If the fault persists, replace the optical module with a normal one of the same type to check whether the optical module is faulty. If the fault persists, collect log

How To Read Optical Module Information On Huawei Switches

Optical modules are widely used in switches, network interface cards (NICs), routers, and other communication devices. During use, reading optical module information helps understand

Optical Module Solutions for Huawei S5700/S5720 Series Switches

This article summarizes several solutions for using optical modules with switches and common problems encountered during usage, along with specific solutions.

Troubleshooting for Optical Modules on Huawei Switch

When the power of optical ports connecting two switches is abnormal, either of the following situations occurs: When the transmit/receive power of the optical ports

ALM-3276800022 Indicates that optical module power abnormal

Run the display transceiver verbose command to check the power of the optical module. Check whether the interface status and data forwarding are normal.

Optical Module Troubleshooting

Run the display interface transceiver verbose command to display diagnostic information about the optical module on the local interface. Check whether the diagnostic information displays alarms

Typical Troubleshooting Cases of Optical Module

If possible, remove and reinstall the optical modules to check whether the fault is rectified. If the fault persists, run the reboot command to restart the switch or power cycle the switch, and check whether

How To Check If Interconnected Optical Ports Cannot

The optical module cannot be installed in an optical interface because the optical module structure is non-standard. The structure and size of some non-certified

Optical Module: Typical Optical Module Troubleshooting Procedure

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

If the optical module is faulty, replace it with the spare part. If the fault is caused by the configuration or environment, advise the customer to optimize the configuration or environment.

ALM-3276800022 Indicates that optical module power abnormal 136195

If not, replace the local optical module with a new one to ensure they are of the same type. Add -5 dBm (recommended) attenuators to the optical module. If the problem persists after the

Optical Module Solutions for Huawei S5700/S5720 Series Switches

When using switches, we may encounter many confusions, such as what types of optical modules are needed for different models of Huawei switches, and how to resolve issues encountered

Hardware Management Configuration Commands

display device optical-module wavelength-capability interface display device power display device power system display device temperature display device voltage display disk partition display fabric slot

Huawei Technical Support

Learn how to display optical module information on Huawei devices using specific commands and understand the diagnostic details of optical modules.

Displaying Optical Module Information

Procedure Run the display transceiver [interfaceinterface-typeinterface-number | slotslot-id] [verbose] command to view information about the optical module on a specified interface.

Optical Module: The Device Cannot Display Any Optical Module ...

Call Huawei global service hotline or contact software maintenance engineers to verify the software version. If allowed, reboot the device or power off and restart the device. Services on the

Poor OLT''s Upper-Layer Network Quality

Procedure Check whether the optical module installed in the uplink port on the OLT is functional. Check whether the uplink port is functional. An OLT equipped with

Troubleshooting Guidelines for Optical Modules

If the transmit optical power is abnormal, replace the optical module. Remove and reinstall the optical module. If the fault persists, replace the optical module with a normal one of the same type to check

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

port is disconnected due to optical module faulty

Use the idle optical module on the storage device to exchange with PO and check whether the fault is rectified. If the fault persists, it indicates that the optical module is not faulty. If

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved