Integration of two core switches



Overview

When we enable switch aggregation, our two switches on the core layer become one logical switch: The two core switches will act as a single switch to the outside world when it comes to control plane protocols like ARP, spanning tree, EtherChannel and routing protocols. With the Fortinet solution for integrated networking using FortiLink, the core layer always comprises a set of two to four FortiGate devices and two very high-speed FortiSwitch units, which support a large number of 100-GbE and/or 40-GbE ports with enough capacity to grow the links between them and. We have two 4507s at our core, running HSRP. We have three other 4507s at the edge, plus eight 2950s. All edge switches and WAN routers are connected to both core 4507s. My plan is to configure 2 uplinks on the 3650, one to each core switch. Original connection was wired with Cat 5 and unmanaged switches but we are buying new POE. Chassis aggregation is a Cisco technology to make two switches operate as a single logical switch. It is similar to stacking but meant for chassis switches like the 6500 and 6800 series switches.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Article Content

Core layer | FortiSwitch 7.6.0 | Fortinet Document Library

With 8x100-GbE QSFP28 slots per FortiGate unit, it provides enough capacity to directly connect with 2x100-GbE ports to each of the two core FortiSwitch units at a nonstop forwarding capacity of up to

What is optimal way to connect two core switch/routers

All edge switches and WAN routers are connected to both core 4507s. We have a Port-Group of two wires connecting the core switches together, and we built a VLAN interface (with an IP

Edge switch redundancy to two core switches

I want to provide best redundancy for an access switch (Cisco 3650) when connecting to two core switches (Cisco 9500 series), as show in attached topology. My plan is to configure 2

Connecting Multiple switches to core : r/networking

I''ve worked in large manufacturing facilities where the Core is connected to Distribution switches and they connect the standard layer 2 access switches. My boss was always on at me “upgrade the core

Chassis Aggregation

Chassis aggregation is a Cisco technology to make two switches operate as a single logical switch. It is similar to stacking but meant for chassis switches like the 6500 and 6800 series switches. It is often

Core Switch

For example, it is possible for a pair of network interface cards (NICs) to be dual-homed into a pair of access switches (using NIC teaming), and then one can use MC-LAG to interconnect the access

FortiSwitchOS Switching Reference Architecture Guide

To provide link redundancy, two sets of two switches have an inter-switch link to their closest FortiSwitch neighbor with a second 10-GbE link, forming two distinct loops.

How to Connect Multiple Ethernet Switches

This article will explore three common connection methods: switch cascading, switch stacking, and switch clustering, and will help you determine the best approach based on network

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

How to Connect Multiple Ethernet Switches Using Fiber

In cases where the distance between switches exceeds the total cable length, you can use the LC-LC coupler to connect two fiber optic cables together. For example, insert the connector

Network with inter vlan routing

I have two routers (in my opinion for redundanty like HSRP). They are connected to 2 core switches L3 (in my opinion also for redundanty like HSRP). 2 core switches have connected 2

Dual Core Design

Its not just two core routers. it can be 2 core routers connecting to 2 core switches which are then interconnected with the layers below. You can have two core routers with redundant connection to

Solved: Redunancy with two switches core

Hello everyone, I have a customes have just bougth ttwo switches core (L3), his today diagram network is: Access Switches come to one Switch Core and this connect to a Firewall to

2 locations, 2 core switch stacks, fibre in between, equal cost load ...

They state: "Core switches shall be linked with 2x 1Gbps links bonded into a standard compliant Etherchannel" "Uplinks between access and core switches shall be non-blocking - for

Design recommendation for high availability

How are the Core switches working for redundancy? VRRP? I don''t think you need to worry about how your Access switch paths its traffic - it''s the two cores that need to agree on the

Full Mesh between two L3 Core Switch and 2 Core routers

Respested All, we have one new customer, for which i have to commission new network for them, there are two core router 3945 and two Core L3 switch 4507R, for local lan user i have

Single firewall with 2 core switches

Hi All Following is my requirement. Two different WAN links get connected to the firewall via two routers.(Different ip subnets).I need to get this two wan streams seperatly to the core

HSRP between 2 access switches and 2 core switches

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Hi I am looking for running HSRP between 2 access switches and 2 core switches for client PC and Server network''s next-hop redundancy as per attached setup. As you can see I have used

Two-Tier Core

Prepare switches for deployment in Aruba Central for building a Two-Tier Data Center. The L2 Two-Tier Data Center uses an MC-LAG core for performance and redundancy connected to

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved