Number of interfaces on the aggregation layer switch



Overview

Configure an Aggregate Interface Group Enter the Max Ports (number of interfaces) that are active (1 to 8) in the aggregate group. If the number of interfa.

Key Takeaways

Aggregation layer switches consolidate multiple access layer connections, and each aggregated Ethernet (AE) interface can typically include up to 8 physical member interfaces, depending on the switch model.

Aggregation Layer Switch Overview

An aggregation switch sits between access layer switches and core switches, consolidating traffic from multiple access devices and forwarding it upstream. These switches operate at Layer 2 or Layer 3, providing high throughput, redundancy, and failover capabilities. They often implement link aggregation protocols such as LACP or static link aggregation to combine multiple physical links into a single logical interface, increasing bandwidth and reliability.

Aggregated Ethernet Interfaces

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Aggregated Ethernet (AE) interfaces, also called link aggregation groups (LAGs) or port channels, allow multiple physical Ethernet interfaces to function as a single logical interface. This provides: Increased bandwidth by load balancing traffic across member linksRedundancy, as traffic continues if one member link failsSimplified management, treating multiple links as a single interface Each AE interface can typically include up to 8 physical interfaces, though the exact number depends on the switch or firewall model. For example, Palo Alto Networks firewalls support AE groups with up to 8 interfaces per group, and Juniper switches allow multiple physical interfaces to be combined into a single aeX interface.

Practical Considerations

Interface type and speed: All member interfaces in an AE group must have the same bandwidth (e.g., 1Gbps, 10Gbps, 40Gbps, 100Gbps) and compatible interface types. Redundancy distribution: For high availability, AE members should be distributed across redundant server nodes or switches to ensure failover capability.

Number of A

E groups: The total number of AE interfaces a switch can support depends on the platform and model, which should be verified in the product specifications. In summary, an aggregation layer switch typically supports multiple AE interfaces, each composed of up to 8 physical member interfaces, providing both increased bandwidth and redundancy for uplinks to the core layer. The exact number of interfaces and AE groups depends on the specific switch model and configuration.

Article Content

Configure an Aggregate Interface Group

Enter the Max Ports (number of interfaces) that are active (1 to 8) in the aggregate group. If the number of interfaces you assign to the group exceeds the Max Ports, the remaining interfaces will be in

Aggregate Ethernet (AE) Interface Group

The number of AE interface groups you can add depends on the firewall model. The Product Selection tool indicates the Maximum aggregate interfaces that each firewall model supports. Each AE

aggregated-devices | Junos OS | Juniper Networks

The number of devices you define will be the number of aggregated ethernet interfaces that the system will create which can be configured just like any other ethernet interface. Also you

What is Switch Aggregation, Its Role and Selection Advice

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Compared to access layer switches, aggregation layer switches require higher performance, fewer interfaces, and higher switching speeds. The primary functions of this layer include:

Link aggregation

Combining can either occur such that multiple interfaces share one logical address (i.e., IP) or one physical address (i.e., MAC address), or it allows each interface to have its own address. The former

Aggregation layer | FortiSwitch 7.6.0 | Fortinet Document Library

The most appropriate FortiSwitch unit to form the aggregation layer comprises many 10/25/40 gigabit Ethernet ports to address the access layer and a few 100-GbE ports towards the core layer.

Junos Aggregated Ethernet Example

In Junos, multiple physical Ethernet interfaces can be combined to form a single aggregated Ethernet interface. The name of this interface will be aeX, where X is a number starting at 0 and incrementing

What Is an Aggregation Switch and How to Choose?

When selecting an aggregation switch, you need to consider the uplink port type and number of the network access switches, as well as the downlink port type of the core switch.

LAG configuration guidelines

Configure at least one active mode aggregation in two devices. For a successful static aggregation, make sure the ports at both ends of each link are in the same aggregation state.

Link Aggregation: Static vs Dynamic, LACP, and MLAG

Understand how link aggregation (LACP, MLAG, static vs dynamic) improves bandwidth and redundancy. Learn configuration steps on Cisco and

Link Aggregation: What is it, and How Does it Work?

Link aggregation is a way of bundling a bunch of individual Ethernet links together so they act like a single logical link. Learn more on the Auvik blog

What Are Link Aggregation, LAG, and LACP?

What Is LAG and How Does It Work? Link Aggregation Group (LAG) is the practical implementation of link aggregation, where multiple physical ports are combined into a single logical

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Link Aggregation Configuration

For a fixed switch in V200R009 and later versions, VRRP can be configured on the VLANIF interface, Layer 3 Ethernet interface, and sub-interface. Ensure that each device of the same VRRP group is

Aggregation Switch

Aggregation and core switches Aggregation switches are typically used to connect a number of ToR switches to a core switch/router. The core switch is at the top of the cloud data center network

Link_Aggregation_Config_Guide

1 Link Aggregation Configuration Guide This document describes the Link Aggregation feature supported in Supermicro Layer 2 / Layer 3 switch products. This document covers the Link

Data Center Multi-Tier Model Design

Data Center Core Layer The data center core layer provides a fabric for high-speed packet switching between multiple aggregation modules. This layer serves as the gateway to the campus core where

Link Aggregation and Ethernet Bonding Feature Overview and ...

Link aggregation interfaces have names like ''po1'' and ''sa1'' depending on the aggregation method in use. Ethernet bonding is used to refer to static or dynamic (LACP) aggregation configured on router

SMB Switch: Access Switch vs Aggregation Switch vs Core Switch

SMB switches support common Layer 2 protocols, but the performance and number of interfaces are weak. Access switches, aggregation switches and core switches are another

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved