Optical module transmission 1330



Overview

A single-mode optical module with an SFP+ form factor for LTE equipment. The SFP+ transceiver supports up to 10km link lengths over OS2 SMF via an LC simplex connector. This 10G BiDi SFP+ transceiver, featured with data transmission over a single strand of fiber, the one transceiver transmits a 1330-nm channel and receives a 1270-nm signal, whereas the other BiDi SFP+. Single-mode module, SFP+ WDM 6. 25G, OBSAI/CPRI, LC connector, operating wavelength Tx/Rx: 1330/1270, distance up to 10km. It is designed to work in single-mode optical fiber (SMF) with a maximum distance of 10 km, an optical. Want to learn more?

20km fiber SFP module 10G 1330 modules Conforming to the Small Form Factor Pluggable (SFP) Multisource Agreement, these SFP+ transceivers are designed expressly for high- speed duplex PON communication applications that require 10 Gbps data rates, with the laser transmission portion of the device. *Images are for illustrative purposes. Actual product appearance and specifications may vary.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Article Content

Module SFP+ 6.25G WDM LTE, Tx/Rx 1330/1270nm, 10km (6dB)

A single-mode optical module with an SFP+ form factor for LTE equipment. It is designed to work in single-mode optical fiber (SMF) with a maximum distance of 10 km, an optical budget of 6dB, an LC

SFP-XG-TX1270-RX1330-IN

Home All Products Transmission Switches Optical Modules SFP-XG-TX1270/RX1330-IN 10 Gigabit Single-Mode 20km BIDI Optical Module-TX1270/RX1330 Specification

MT-SFP-LX-SM-1330-20 10GBase-WDM Bi-Directional SFP+ LC Module

modules Conforming to the Small Form Factor Pluggable (SFP) Multisource Agreement, these SFP+ transceivers are designed expressly for high- speed duplex PON communication applications that

HK-SFP+-10G-20-1330

Actual product appearance and specifications may vary. *Product performance is based on testing in a controlled environment. Your results may vary due to several external and environmental factors.

SFP+ BiDi WDM 10GbE 20km Universal Optical

The 10G SFP+ BiDi WDM optical transceiver transmits data over single mode fibre at a distance of up to 20km. The transceiver operates on 1 wavelength and

MaxLink 10G SFP+ optical HP modul, WDM(BiDi), SM,

Maxlink ML-S+3327-10-HPE is a 10G SFP+ WDM module with a Tx 1330 / Rx 1270 wavelength, a single LC connector, and a maximum transmission distance of

SFP+ Ultimode 10 Gbit/s BiDi (WDM) module, single mode, 1270

The ULTIMODE SFP+ module is used to extend the capabilities of network devices with the possibility of realising transmission via optical fibre.

Transceivers 1330 nm Fiber Optic Transmitters, Receivers, Transceivers

Mouser offers inventory, pricing, & datasheets for Transceivers 1330 nm Fiber Optic Transmitters, Receivers, Transceivers.

1270nm/1330nm 60km 10GBase-BX BiDi optical SFP+ | Extended

Reliable 10G BIDI SFP+ modules for high-performance optical networking. The 10GBASE-BX BiDi SFP+ is a 1270nm-TX / 1330nm-RX optical transceiver designed for 10Gbps high-speed data transmission

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

GlobalFoundries'' Unveils Optical Module Solution Targeting CPO

The SCALE CPO solution uses both coarse and dense wavelength-division multiplexing (CWDM and DWDM) for bi-directional data transmission over each optical fiber, delivering significant

Huawei QSFP28 100G CWDM4 Optical Transceiver Accelerates High

Huawei QSFP28 100G CWDM4 optical transceiver modules are becoming an essential solution for enterprises, cloud providers, telecom operators, and hyperscale data centers seeking

Broadcom Sian3 and Sian2M: 200G/lane optical

Analyzing Broadcom''s Sian3 and Sian2M 200G/lane DSP technologies. Sian3 (3nm/SMF) and Sian2M (5nm/MMF) support 800G and 1.6T

CPO Optical Transmission inevitable is changing data transmission ...

Due to the supply shortage in AI data center construction, there''s also a shortage of CPO optical transmission modules. With few suppliers to begin with, market demand is booming and is

Small Form-factor Pluggable

Small Form-factor Pluggable connected to a pair of fiber-optic cables Small Form-factor Pluggable (SFP) is a compact, hot-pluggable network interface module

LPO vs NPO vs CPO: The Evolution of Optical Interconnects in AI

Today, 800G optical transceivers are widely deployed in modern AI data centers to support high-performance GPU networking. As AI clusters continue to scale, the industry is moving

SFP+ Module: Ultimode 10Gbit/s BiDi (single-mode, 1270nm/1330nm,

SFP/SFP+ modules (Small Form-factor Pluggable) convert electrical signals to optical transmission standards and vice versa. The module supports data rates up to 10 Gbit/s via one single-mode fiber

10G BIDI SFP+ 1330nm-TX/1270nm-RX 10km Transceiver Datasheet

Description The SFP-10G-BX series single mode transceiver is small form factor plug module for duplex optical data communications such as 10GBASE-LR/LW defined by IEEE 802.3ae. It is with the SFP+

Chinese Funds Lift Investment in Optical Module Stocks Amid AI

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

The high-speed transmission capacity of massive data is the key to determining the ceiling of AI computing power. Optical communication uses a laser as the information carrier and

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved