# Optocoupler Operational Amplifier



## Overview

The earliest opto-isolators, originally marketed as light cells, emerged in the 1960s. They employed miniature incandescent light bulbs as sources of light, and cadmium sulfide (CdS) or cadmium selenide (CdSe) photoresistors (also called light-dependent resistors, LDRs) as receivers. In applications where control linearity was not important, or where available current was too low for driving an incandescent bulb (as was the case in vacuum tube amplifiers), it was replaced with a neon lamp.

## Key Takeaways

Optocouplers transfer electrical signals between isolated circuits using light, and operational amplifiers can be used with them to create precise, linear isolation amplifiers for analog signals.

### Optocouplers Overview

An optocoupler (also called an opto-isolator or photocoupler) is a semiconductor device that transfers electrical signals between two electrically isolated circuits using light as the medium. Typically, it consists of an LED emitter and a photodetector such as a phototransistor, photodiode, or photoresistor enclosed in a single package. Optocouplers protect sensitive circuits from high voltages and transients, providing galvanic isolation up to several kilovolts, and are widely used in digital and analog applications.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Operational Amplifiers with OptocouplersOperational amplifiers (op-amps) are often used with optocouplers to linearize and amplify signals in isolation circuits. In precision analog isolation amplifiers, the op-amp can act as a servo amplifier controlling the LED current in the optocoupler. This configuration ensures that the output photocurrent accurately tracks the input voltage, maintaining high linearity and stability.

## Key Applications

Linear Isolation Amplifiers: Using optocouplers like the IL300 or HCNR201, op-amps can create isolation amplifiers that accurately transfer low-level analog signals while maintaining galvanic isolation. These are used in industrial sensors, medical instrumentation (EEG, ECG), and communication systems. Feedback Control in Power Supplies: In linear or switch-mode power supplies, optocouplers combined with op-amps provide isolated feedback loops.

The op-amp controls the LED to maintain a DC-transparent feedback signal, ensuring stable output voltage while isolating the high-voltage side from the low-voltage control circuitry. Analog Signal Conditioning: High-linearity optocouplers like the HCNR201 use two matched photodiodes. One photodiode monitors the LED output to compensate for nonlinearity and drift, while the other provides the output signal.

Op-amps process these signals to achieve precise, low-noise analog isolation.

## Design Considerations

Linearity: Using a feedback photodiode and op-amp servo loop improves linearity and reduces LED drift. Bandwidth: Optocoupler bandwidth and op-amp response must match the application requirements, especially in high-speed or audio circuits. Isolation Voltage: Ensure the optocoupler's isolation rating meets safety and regulatory standards.

Temperature Stability: Op-amp compensation and matched photodiodes help maintain performance across temperature variations.

## Summary

By combining optocouplers with operational amplifiers, engineers can design circuits that provide safe electrical isolation while accurately transferring analog or digital signals. This combination is essential in applications requiring high precision, safety, and noise immunity, such as medical instrumentation, industrial sensors, and isolated power supply feedback systems.

*© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved*

## Article Content

Precision Analog Isolation Amplifier Using HCNR201 Optocoupler

An operational amplifier (OP AMP) labeled as U3 is used with PD1 optocoupler to sense light intensity output from the optocoupler''s LED and automatically adjusts the current that flows

Opto-isolator

OverviewTypes of opto-isolatorsHistoryOperationElectric isolationTypes of configurationsSources

The earliest opto-isolators, originally marketed as light cells, emerged in the 1960s. They employed miniature incandescent light bulbs as sources of light, and cadmium sulfide (CdS) or cadmium selenide (CdSe) photoresistors (also called light-dependent resistors, LDRs) as receivers. In applications where control linearity was not important, or where available current was too low for driving an incandescent bulb (as was the case in vacuum tube amplifiers), it was replaced with a neon lamp. These devices (or

Using Opto Couplers

The main purpose of an optocoupler interface is to completely isolate the input circuit from the output circuit, which normally means there will be two completely

Optocoupler Tutorial and Optocoupler Application

This type of optocoupler configuration forms the basis of a very simple Solid State Relay application. It can be used to control any AC mains

Optoelectronic Feedback Control Techniques for Linear and Switch

This optical isolation amplifier uses an operational amplifier (U1) as an electro-optical servo amplifier that controls the LED current. The servo photodiode is operated in the photovoltaic mode and is zero

Optocoupler Operation

To link circuits such as audio amplifiers where signal voltages are rapidly changing, but saturation and distortion need to be avoided, optocouplers can transfer signals using Analogue Mode so that audio

LOC Series Linear Optocouplers

This application note describes isolation amplifier design principles for the LOC Series linear optocoupler devices. It describes the circuit operation in photoconductive and photovoltaic modes and provides

*© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved*

operational amplifier

Optocoupler would be used if you need isolation. In deed you will normally have an option to reduce voltage by simply putting lower resistor on the secondary side.

HCNR200 and HCNR201: High-Linearity Analog Optocouplers Data

Figure 13a illustrates the basic circuit topology for implementing a simple isolation amplifier using the HCNR200/201 optocoupler. Besides the optocoupler, two external op-amps and two resistors are

How Photocouplers / Optocouplers Are Used | Renesas

This is the same as using amplifier circuits in audio amplifiers or operational amplifiers that have gains 100 to 1000 times higher than the gain that is actually required. These high gains are then lowered by

Optocoupler Circuits | Nuts & Volts Magazine

Simply described, an optocoupler device is a sealed, self-contained unit that houses independently-powered optical (light) Tx and Rx units, that can be coupled together optically.

Optocouplers Desig

application. Additionally, optocoupler vendors have devel-oped a wide variety of devices that have various types of interfaces to suit many diferent pplications. At Avago, for example, Type 1 AlGaAs

operational amplifier

What is the best route? Optocoupler or opamp (if opamp, which one?) I need to reduce this 5.8V pulse generator to 0.84V Have an automotive application I am trying to find a solution.

Optocoupler Circuits, Working, Characteristics, Interfacing

Optocouplers become an effective replacement for relays, and for transformers for interfacing digital circuits stages. Additionally, Optocoupler frequency response prove to be

Designing Linear Amplifiers Using the IL300 Optocoupler

Isolation amplifiers using the IL300 are not plagued with the drift problems associated with standard phototransistors. The following analysis will show how the servo operation of the IL300 eliminates the

Application Examples

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

INTRODUCTION Optocouplers are used to isolate signals for protection and safety between a safe and a potentially hazardous or electrically noisy environment. The interfacing of the optocoupler between

Activity: Optocouplers. [Analog Devices Wiki]

Activity: Optocouplers. Objective: In this activity you will construct an optocoupler from an infra-red LED and an NPN photo transistor. You will investigate the operation of an optocoupler based analog

Optocoupler Application Note

Optocoupler Application Note Example of a High Voltage OP AMP Circuit Notes / Application Considerations • Complimentary transistor pair (Q1 and Q2) drives optocoupler LED''s producing

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

## Additional source notes

The earliest opto-isolators, originally marketed as light cells, emerged in the 1960s. They employed miniature as sources of light, and (CdS) or (CdSe) photoresistors (also called light-dependent resistors, LDRs) as receivers. In applications where control linearity was not important, or where available current was too low for driving an incandescent bulb (as was the case in vacuum tube amplifiers), it was replaced with a . These devices (or …

*© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved*

## Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved