
Ortel optical emission module



Overview

The Model 1786 from Ortel is a 1550-nm laser module made for use as a continuous wavelength coherent optical source for optical sensing and lidar systems. Additionally, we offer access to volume manufacturing sites providing assembly and logistics services across all markets. The 755MM-U may also be used up to 20 km with a lower channel load of 11 analog Contextual Info:. An Ortel Laser Module is a high-performance solid-state laser system designed for precision applications across scientific, medical, industrial, military, and telecommunications fields. These modules are known for their reliability, compact design, and superior beam quality, making them ideal for. With 900um-buffered single-mode fiber, without fiber connector. Features 5 MHz—200 MHz frequency range Flat response to ± 0. 5 dB High optical responsivity Ultra low optical return loss 75 OHM impedance-matched Applications Return-path CATV receivers New. 65USPS Priority Mail Small Flat Rate Box. Delivery times may vary, especially during peak.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Article Content

Laser, Photodiodes and Receivers from EMCORE

ORTEL''s optical sensing components can be custom designed in a variety of form factors to integrate into a wide range of industrial applications including autonomous vehicles, oil and gas exploration,

Precision and Quality: Sourcing ortel laser module for Laser Systems

Upgrade your business with high-quality ortel laser module designed for precision and durability. Enhance productivity and efficiency with reliable parts tailored for optimal performance.

Lightwavestore > Analog Receiver > 1.3/1.55um fiber

With 900um-buffered single-mode fiber, without fiber connector. 14-pin DIL package. Features 5 MHz—200 MHz frequency range Flat response to ± 0.5 dB High optical responsivity Ultra low optical

Ortel 28600-C02 10 GB/s, 2.92 mm (K), -20 dBm, Optical Receiver

I purchased a discontinued fiber optic ring light described as being “new,” and I was extremely impressed: the item was in my hands Analog Receiver > 1.3/1.55um fiber

With 900um-buffered single-mode fiber, without fiber connector. 14-pin DIL package. Features 5 MHz—200 MHz frequency range Flat response to ± 0.5 dB High optical responsivity Ultra low optical

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved