Stlinkv2 connection port



Overview

Guide: Connecting your debugger Connecting Via SWD HeaderConnecting to JTAG HeaderConnecting to GPIO PinsThe easiest way to connect your development board.

Key Takeaways

The ST-LINK/V2 connects to target microcontrollers via USB to the PC and SWIM (STM8) or JTAG/SWD (STM32) interfaces to the target board.

USB Connection to PC

The ST-LINK/V2 uses a USB standard-A to Mini-B cable to connect to a computer. This interface allows communication with development environments such as STM32CubeIDE for STM32 or STVD/STVP for STM8 microcontrollers, enabling programming, debugging, and firmware updates. Target Board ConnectionsSTM8 MicrocontrollersSWIM Interface: The ST-LINK/V2 supports the Single Wire Interface Module (SWIM) for STM8 devices.

Connector Options: Standard ERNI 4-pin SWIM connector: A flat ribbon cable connects the ST-LINK/V2 to the target board using the ERNI connector. Low-cost 2. 54 mm pitch connector: Individual wires can be connected to TVCC, SWIM, GND, and SWIM-RST pins if the target board lacks a standard connector.

Pinout: Includes power (TVCC), ground (GND), SWIM data, and reset (SWIM-RST) signals. STM32 MicrocontrollersJTAG/SWD Interface: The ST-LINK/V2 communicates with STM32 devices using JTAG or Serial Wire Debug (SWD). Connector: 20-pin flat ribbon cable: Standard connection to the target board for programming and debugging.

SW

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

V (Serial Wire Viewer): Optional interface for real-time trace and debugging. ST-LINK/V2-ISOL VariantThe ST-LINK/V2-ISOL provides digital isolation between the PC and the target board, supporting the same SWIM, JTAG/SWD, and SWV interfaces. It is suitable for sensitive boards or higher voltage applications.

SummaryPC Connection: USB Mini-BSTM8 Target: SWIM via ERNI 4-pin or low-cost 2. 54 mm connectorSTM32 Target: JTAG/SWD via 20-pin flat ribbonOptional: ST-LINK/V2-ISOL for isolated connections These ports ensure reliable communication for programming, debugging, and monitoring STM8 and STM32 microcontrollers. Proper cable selection and pin alignment are essential to avoid damage and ensure correct operation.

Article Content

Guide: Connecting your debugger

Connecting Via SWD HeaderConnecting to JTAG HeaderConnecting to GPIO PinsThe easiest way to connect your development board to your debugger is by using the 4-pin SWD header, if present. This header is usually a male dupont header, but female headers are also used. The header exposes a ground pin, a +3.3V pin, a clock pin, and a data pin. Note: There is no particular order in which these pins are arranged. Warning: See more on stm32-base ManualsLib

ST -LINK/V2 USER MANUAL Pdf Download | ManualsLib

4.1.1 Standard ERNI connection with SWIM flat ribbon Figure 5 shows how to connect the ST-LINK/V2 if a standard ERNI 4-pin SWIM connector is present on

ST-Link connection

ST-LINK driver ¶ To connect to an STM32 device through a debug interface using ST-LINK/V2, ST-LINK/V2-1, ST-LINK-V3, or ST-LINKV3Power, install the ST-LINK driver by running the

STM32-St-Link-V2-Setup

After the uploading finished the board will be disconnected from the software so don''t panic you can connect it again. Here''s my hex file for blinking LED on pin B9

ShillehTek ST-LINK V2 Manual – Flash & Debug STM32

Plug it into your PC''s USB port, connect the four-wire SWD or SWIM header to your target board, and you can flash firmware, debug step-by-step, set breakpoints, and read RAM and registers in real time

STM32 Debugging With ST-Link v2 SWD | Serial Wire Viewer

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

The ST-Link v2 Programmer / Debugger On The Bottom Side OF The Board. It''s The One Connected To The USB Port On The Board As Well. Obviously, no extra hardware is needed when

STMicroelectronics ST-LINK/V2 In Circuit Debugger

The Tag-Connect adapter and cable provide a simple and reliable means of connecting ST-LINK/V2 or ST-LINK/V2-ISOL to the PCB without

ST-LINK/V2 in-circuit debugger/programmer for STM8 and STM32

The Tag-Connect adapter and cable provide a simple reliable means of connecting ST-LINK/V2 or ST-LINK/V2-ISOL to your PCB without requiring a mating component on application PCB.

ST-LINK/V2 in-circuit debugger/programmer for STM8 and STM32

For development of applications based on STM8 microcontrollers, the ST-LINK/V2 can be connected to the target board by two different cables, depending on the connector available on the application board.

Do I need the St-link ? : r/embedded

So I got this board (STM32F103C6T6) with no st-link connector (programmer/debugger) so, my question is : What do I need it for ? Just the first time to build the bootloader driver on it and then can program

Electronic Components and Parts Search | DigiKey

Search DigiKey''s expansive product index to find detailed product information and pricing on millions of in-stock products. We get technical, so you can search with

HMS Networks

HMS creates products that enable industrial equipment to communicate and share information with software and systems. In short: Hardware Meets Software™.

STM32 ST-LINK Utility installation download program configuration

Download STM32 program using ST-LINK 1. Circuit connection There are three main download and debug interfaces for STM32: JTAG, SW, and serial port (cannot be debugged). The information of

NUCLEO-F446RE

Nucleo ST-LINK/V2 driver installation and firmware upgrade Install the ST-LINK/V2 driver before connecting the Nucleo board to your PC the first time. Follow this LINK for all details. For optimum

ST-LINK/V2 in-circuit debugger/programmer for STM8 and STM32

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Introduction The ST-LINK/V2 is an in-circuit debugger/programmer for the STM8 and STM32 microcontroller families. The single wire interface module (SWIM) and JTAG/serial wire debugging

Terms of use

Thank you for accessing the website of IC-Components We respects your privacy and takes your online safety seriously. To better protect your privacy, we provide the notice below explaining our

ST-LINK/V2 | Tool

JTAG cable for connection to a standard JTAG 20-pin 2.54 mm pitch connector JTAG support SWD and serial wire viewer (SWV) communication support Direct firmware update support (DFU) Status LED

Overview of ST-LINK derivatives

ST-LINK/V2-A, for mass storage ST-LINK/V2-B, for mass storage and Virtual COM port Finally, an STLINK-V2EC version completes the ST-LINK/V2 generation with a USB Type-C® connection

DIY STM32 Programmer (ST-Link/V2-1)

In short, the ST-Link/V2.1 devices offer a few extra features: Serial Wire Trace (SWO) Virtual serial port Mass storage All features that, while not absolutely essential, does come quite handy. Another

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved