To bind a MAC address to the core switch



Overview

To add a static MAC address, run mac address-table static mac-addr vlan vlan-id interface interface-id.

Key Takeaways

MAC addresses can be bound to core switches using static, sticky, or DHCP-based methods to control device access and enhance network security. 1.

Static MAC Address Binding

Static binding involves manually assigning a MAC address to a specific switch port. This ensures that only the designated device can communicate through that port. On Cisco switches, this can be configured using port security commands: Switch(config)# interface FastEthernet0/1Switch(config-if)# switchport port-securitySwitch(config-if)# switchport port-security mac-address 00AA.

BBCC. DDEESwitch(config-if)# switchport port-security maximum 1Switch(config-if)# switchport port-security violation restrict This method is highly secure but administratively intensive, especially in large networks, because each MAC must be manually entered and updated if devices move. 2.

Sticky MAC Address Binding

Sticky MA

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

C binding allows the switch to learn MAC addresses dynamically and then save them in the running configuration. This combines the convenience of dynamic learning with the security of static binding: Switch(config-if)# switchport port-security mac-address sticky Once learned, the MAC addresses are retained across reboots if saved to the startup configuration. This method is useful for environments where devices may occasionally move but still require port-level security.

3. DHCP-Based MAC BindingFor larger deployments, especially with IP phones or hundreds of devices, binding MAC addresses via DHCP reservations is more scalable.

The DHC

P server assigns a specific IP address to a device based on its MAC address. On Cisco core switches acting as DHCP servers:ip dhcp pool VOIP host 172. 16.

10. 10 255. 255.

254. 0 client-identifier 01: 00: 50: 54:xx:xx:xx hardware-address 5405.db39.f302 This ensures that only the specified MAC address receives the reserved IP, preventing unauthorized devices from obtaining network access. 4.

Considerations for Core Switch Deployment

Port Security Limits: Core switches often handle uplinks and multiple VLANs; binding too many MAC addresses per port can impact performance. Device Mobility: Sticky or DHCP-based binding is preferable in environments with mobile devices. Security Enforcement: Combine MAC binding with VLAN segmentation and access control lists (ACLs) for enhanced security.

Monitoring and Maintenance: Regularly audit MAC tables and DHCP reservations to prevent stale entries and ensure network integrity. By combining these methods, network administrators can securely control which devices connect to the network, reduce unauthorized access, and maintain efficient IP address management.

Article Content

MAC Address Configuration Commands

To add a static MAC address, run mac address-table static mac-addr vlan vlan-id interface interface-id. To cancel the static MAC address, run no mac address-table static mac-addr vlan vlan-id interface

How to configure MAC with IP bindings in cisco 2960 switch

You want to bind the DHCP leased address to the device (MAC address) and refrain the user from changing this IP statically? I so then use the host pool config proposed by Leo and

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

configuring_mac_address

The following example shows how to limit the number of MAC addresses to 100 in VLAN 10, and configure the switch to drop packets of new source MAC addresses when the limit is exceeded.

Does a Switch Support the Binding of One MAC Address and Multiple

A switch supports the binding of one MAC address and multiple IP addresses. If you need to bind non-contiguous IP addresses to a MAC address, enter 1 to 10 IP addresses in the command. For

Switch port and MAC address binding (based on Cisco Simulator)

For security and convenience management, you need to bind the MAC address to the port, that is, the MAC address is bound to the port, the data stream of the MAC address can only be entered from the

MAC Address Table On a Cisco Switches

The switch keeps track of the other Ethernet interfaces on the network to which it is linked in the MAC address table. Instead of broadcasting the data over all ports, the table allows the switch

Configuring IP-MAC Address Binding

In the controller software Release 5.2 or later releases, the controller enforces strict IP address-to-MAC address binding in client packets. The controller checks the

IP to MAC address binding in 3560G Switch

Some users are trying to enter the permitted IP address and using Internet, I want to bind permitted IP with the MAC address of User PC on the core switch.. to do so,,i found a configuration

How to bind mac-address to port without port security

Hi Team How to bind mac address to a switch port without port security? Is there any way that I could bind the port with mac address? regards Pragash

How to find port it connected to a switch using mac-address/ip add ...

On a Cisco switch, you can issue the “sh cam 00-0d-60-cb-44-5d” command. The output should tell you the VLAN they are on, the MAC address you entered and the port that MAC shows up

How Is A MAC Address Used By A Network Switch

Introduction Understanding how a network switch utilizes MAC addresses is crucial for comprehending the fundamental operations of modern

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

MAC to IP Address Binding in cisco 3560 Switch

Hi, We have configured Cisco 3560 Switch as DHCP server. Created VLAN 2-20. VLAN 4 is for wifi users. remaining all VLAN''s for wired LAN users. Our airm is to assign fixed IP address

Configuring IP-MAC Address Binding

Information About Configuring IP-MAC Address Binding In the controller software Release 5.2 or later releases, the controller enforces strict IP address-to-MAC address binding in client packets. The

Switch – Trace device Mac Address to Port number

Switch – Trace device Mac Address to Port number Sometimes it can be a pain to trace back which device is connected to which port on the Switch ? Especially when you have multiple

Assigning a MAC or IP address to a Switch port

Is it possible to assign a single MAC or IP address to a 3548XL switch port so that machines with other MAC or IP address cannot connect to the network thro that particular port.

Bind IP address to switch port without Learning the MAC address

We are facing a bit of an issue. What have several servers, and what we want is to prevent one from stealing the IP of another server, but without learning the MAC address of the

From core : Finding Mac address and port interface of the end device ...

The mac table on the core will only contain addresses layer 2 adjacent through the core switch and show on the interface from core to the access switch where the device is located.

Configure MAC-Based Access Control List (ACL) and Access Control

It blocks or allows users to access specific resources. An ACL contains the hosts that are permitted or denied access to the network device. Media Access Control (MAC)-based Access

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved

Contact Us

Continue your research online:

Website: https://kenhardtprimary.co.za
Technical inquiry: https://kenhardtprimary.co.za/project-desk.html
African project coordination: Century City, Cape Town, Western Cape, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 KENHARDT OPTICAL NETWORKS - All rights reserved